

W-25HC Spray-All

MODEL # 970225HC

OVERVIEW

The W-25HC Spray-All is a "high concentrate" spray applicator that will achieve strong dilution ratios for the toughest cleaning jobs. This venturi injection system uses standard city water pressure (35 - 125 PSI) to draw and blend chemical concentrate into the water stream to create a very strong chemical solution. The diluted solution is then projected through the discharge hose and fan nozzle as a uniform spray on to a variety of surfaces. Weaker dilution ratios are achieved with metering tips. With a flow rate of just over 1 gallon per minute, this unit is great for spraying virtually any sized area or object quickly and completely.

Key Features

- Achieve strong chemical concentrations up to 2.5 to 1
- Weaker dilution ratios controlled by precision metering tips
- * Creates a medium volume spray (1.3 GPM @ 40 PSI)
- Fan pattern nozzle for fast coverage
- Handles tough jobs quickly with minimal over-spray
- Chemical resistant wetted components ensure years of outstanding performance with minimal maintenance
- Industrial-strength design holds up in tough environments
- Use it where 35-125 PSI water is available
- Available with a lower flow rate (#970220HC)
- See other Lafferty Spray-Alls and more chemical applicators in Catalog 1

Includes

- Stainless steel mounting bracket
- Stainless steel inlet and discharge ball valves
- Machined polypropylene injector body
- 20 color-coded metering tips for weaker dilution ratios
- 50' discharge hose, polypropylene wand and stainless steel fan nozzle

OPTIONS

Stainless Steel Hose Rack

Large	#224150
Stainless Steel Jug Racks	
1 Gallon Round/Square	#224200
1 Gallon Round/Square Locking	#224200-L
2 ½ Gallon (8 ½" x 10 ½")	#224210
5 Gallon (12" x 12")	#224215
5 Gallon Round Locking	#224216

Safe Flow Lid™ for 1 Gallon Jugs

Lid, Suction Tube, and Strainer #709101

Alternate Check Valve - EPDM Standard

Check Valve, Chemical, PP/Viton, 1/4" #491315

APPLICATIONS

- Heavy Degreasing
- Agriculture/Horticulture
- Food & Beverage
- Hood & Vent
- Industrial
- Metal Processing
- Paper Mill
- And Many Other Applications!







REQUIREMENTS

Chemical Concentrate

Water

 Temperature
 up to 160°F

 Pressure
 35 to 125 PSI

 Flow
 1.3 GPM @ 40 PSI

Supply Line 1/2"

Hose 1/2" ID x 50'

Nozzle 2550

Dilution Ratio Range 297:1 to 3:1 @ 40 PSI



Distributed by Tec Team LLC 800-700-2530 www.tecteamllc.com

info@tecteamllc.com